

B₁
(amended)

in the stem portion 55 of the outer joint ring 51 larger than the outer diameter d_1 of the C-shaped clip 77. This would make it possible to allow said clip 77 to be mounted to or dismounted from the shaft bore 82 of the stem portion 55 with a tool such as snap ring pliers.

IN THE CLAIMS:

Please amend claims ~~10-13~~, ~~15~~, ~~17~~, and ~~18~~ as follows:

Sub C-2 > 10. (Amended) A drive wheel bearing assembly according to claim 9, wherein a stem portion of the outer joint ring of said fixed type constant velocity universal joint is made hollow, and the hollow portion is allowed to communicate with a house portion of the outer joint ring.

B₁₂

11. (Amended) A drive wheel bearing assembly having a fixed type constant velocity universal joint, coupled to a wheel bearing, mounted to one end portion of an intermediate shaft, and a sliding type constant velocity universal joint, coupled to a differential, mounted to the other end portion of said intermediate shaft,

§ wherein an allowable plunging down to a bottom portion of an outer joint ring of said sliding type constant velocity universal joint is set to at least a width of an inner joint ring of said fixed type constant velocity universal joint at a minimum operative angle of the sliding type constant velocity universal joint,

12 wherein a stem portion of the outer joint ring of said fixed type constant velocity universal joint is made hollow, and the hollow portion is allowed to communicate with a house portion of the outer joint ring,

AS 10-1-02
wherein an end cap is mounted to a communicating region between the hollow portion of said stem portion and said ^{hollow} mouse-portion, and a communicating portion is formed substantially at a center of the end cap.

12. (Amended) A drive wheel bearing assembly according to claim 9, wherein said wheel bearing is plastically connected to the outer joint ring of said fixed type constant velocity universal joint.

Be (wind)
Sub E 13. (Amended) A drive wheel bearing assembly according to claim 9, wherein a seal boot is mounted on a stub shaft or on an outer diameter portion of the other end portion of said intermediate shaft.

Sub C 3 15. (Amended) A drive wheel bearing assembly according to claim 9, wherein one of a plurality of rows of races in said wheel bearing is formed on an outer diameter portion of a hub ring constituting the wheel bearing, and another race is formed on an outer diameter portion of a separate inner ring engaging the outer joint ring of said fixed type constant velocity universal joint.

Sub C 4 17. (Amended) A drive wheel bearing assembly according to claim 9, wherein at least one of a plurality of rows of races of said wheel bearing is formed integrally on an outer diameter portion of the outer joint ring of said fixed type constant velocity universal joint.